



PAPER ID-410836

Printed Page: 1 of 2  
Subject Code: KME501

Roll No:

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|

**B.TECH**  
**(SEM- V) THEORY EXAMINATION 2021-22**  
**HEAT AND MASS TRANSFER**

Time: 3 Hours

Total Marks: 100

Note: 1. Attempt all Sections. If require any missing data; then choose suitably.

## SECTION A

1. Attempt all questions in brief. 2 x 10 = 20

| Q no. | Question  | Marks | CO |
|-------|---|-------|----|
| a.    | What is the difference between thermodynamics and heat transfer?            | 2     | 1  |
| b.    | How the thermal conductivity of material is defined? What are its units?    | 2     | 1  |
| c.    | What is meant by transient heat conduction?                                 | 2     | 2  |
| d.    | Explain effectiveness and efficiency of fin.                                | 2     | 2  |
| e.    | What is turbulent flow? Define it.  | 2     | 3  |
| f.    | Define Reynolds's number, also write the significance of Reynolds's number. | 2     | 3  |
| g.    | Define Stefan Boltzmann's law.  | 2     | 4  |
| h.    | Explain black body, opaque body, white body and grey body also.             | 2     | 4  |
| i.    | How heat exchangers are classified?   | 2     | 5  |
| j.    | What are the various modes of mass transfer?                                | 2     | 5  |

## SECTION B

2. Attempt any three of the following:

| Q no. | Question  | Marks | CO |
|-------|---|-------|----|
| a.    | Derive an expression for heat conduction through a composite wall.  | 10    | 1  |
| b.    | It is required to heat oil to about 300°C for frying purpose. A ladle is used in the frying. The section of the handle is 5 mm x 18 mm. The surroundings are at 30°C. The conductivity of the material is 205 W/m°C. If the temperature at a distance of 380 mm from the oil should not reach 40°C, Determine the convective heat transfer coefficient. | 10    | 2  |
| c.    | Differentiate between:-<br>(i) Natural and forced convection.<br>(ii) Hydrodynamic and thermal boundary layer thickness.  | 10    | 3  |
| d.    | A 70 mm long circular surface of a circular hole of 35 mm diameter maintained at uniform temperature of 250°C. Find the loss of energy to the surroundings at 27°C, assuming the two ends of the hole to be as parallel discs and the metallic surfaces and surroundings have a black body characteristics.   | 10    | 4  |
| e.    | Derive an expression for effectiveness by NTU method for parallel flow.   | 10    | 5  |

## SECTION C

3. Attempt any one part of the following:

| Q no. | Question  | Marks | CO |
|-------|---|-------|----|
| a.    | Derive a general heat conduction equation for Cartesian co-ordinate. And also draw the temperature-thickness profile for it.  | 10    | 1  |
| b.    | A mild steel tank of thickness 12 mm contains water at 95°C. The thermal conductivity of mild steel is 50 W/m°C, and the heat transfer coefficients for the inside and outside the tank are 2850 and 10 W/m <sup>2</sup> °C, respectively. If the atmospheric temperature is 15°C, calculate:<br>(i) The rate of heat loss per square meter of the tank surface area.<br>(ii) The temperature of the outside surface of the tank. | 10    | 1  |

