Printed Pages-4

ECE035

(Following Paper ID a	nd Roll No	. to be	filled in y	our Ansv	ver Book)
PAPER ID : 2688	Roll No.				

B.Tech.

(SEM. VII) ODD SEMESTER THEORY EXAMINATION 2013-14

ENGINEERING HYDROLOGY

Time : 3 Hours

Total Marks: 100

Note :- Attempt all questions. All questions carry equal marks. If required any missing data; then choose suitably.

- 1. Attempt any four parts of the following : $(5 \times 4 = 20)$
 - (a) What is meant by hydrological cycle ? How can the parameters of the cycle be written in an equation form ? Draw a neat diagram to illustrate your answer.
 - (b) A one-day rainfall of 100 mm at a station was found to have a return period of 50 years. Determine the probability that a one-day rainfall of this or larger magnitude will occur atleast once in 20 successive years.
 - (c) What is the purpose of Water Budget Equation in Hydrology? Also give the expression for the water budget of a catchment for a time interval Δt and write in brief about all the associated terms in this equation.
 - (d) A catchment has six rain gauge stations. In a year, the annual rainfall recorded by the gauges are as follows :

Station	A	В	C D		E	F	
Rainfall (cm)	82.6	102.9	180.3	110.3	98.8	136.7	

For a 10% error in the estimation of the mean rainfall, calculate the optimum number of stations in the catchment.

ECE035/DNG-51799

[Turn Over

- (e) What is probable maximum precipitation over a basin ? Explain any one of the approaches to estimate the probable maximum precipitation value.
- (f) What is an intensity-duration curve and how will you proceed to derive such a curve for a given frequency at a rain gauge station from the available data of worst storms of different durations kept for a sufficient number of cycles.
- 2. Attempt any four parts of the following: $(5 \times 4 = 20)$
 - (a) What are the analytical methods to determine the lake evaporation ? Explain the 'Energy Budget Method' to calculate this.
 - (b) Write about the I.S.I. Evaporated Pan with the help of its neat sketch.
 - (c) Discuss about the empirical relationship for finding out the net radiation value used in the Penman's equation.
 - (d) Show, how the decrease of the ratio AET/PET with available moisture depends upon the type of soil and rate of drying ?
 - (e) The infiltration capacity in a basin is represented by Horton's equation as $f_p = 4.0 + e^{-3t}$; where f_p is in cm/h and t is in hours. Assuming the infiltration to take place at capacity rates in a storm of 60 minutes duration, estimate the depth of infiltration in the first 15 minutes and in the second 45 minutes of the storm.
- 3. Attempt any two parts of the following : $(10 \times 2 = 20)$
 - (a) Write in brief the SCS-CN method for estimating the runoff volume. The peak of flood hydrograph due to a 3-h duration isolated storm in a catchment is 270 m³/s. The total depth of rainfall is 5.9 cm. Assuming an average infiltration loss

ECE035/DNG-51799

2

of 0.3 cm/h and a constant base flow of 20 m³/s, estimate the peak of the 3-h hydrograph (UH) of this catchment. If the area of the catchment is 567 km²; determine the base width of the 3-h unit hydrograph by assuming it to be triangular in shape.

(b) Explain the factors that affect the runoff from a catchment area. How will you estimate the amount of runoff ? A 4-hour storm in a basin producing 10 cm of runoff results the following flows in the stream;

Time (hour)	0	2	4	6	8	12	16	20	
Flow (cumec)	0.0	2.44	8.10	13.50	11.34	6.75	2.70	0.0	

Calculate the peak flow and the time of its occurrence of the flood created by an 8-hour storm in the basin which produces 5 cm of runoff during first 4-hours and 7.5 cm runoff during the second 4-hours. Assume base flow is negligible.

- (c) Explain with the help of neat sketches, the flow duration curve method and mass curve method to measure the runoff.
- 4. Attempt any two parts of the following : $(10 \times 2 = 20)$
 - (a) What do you mean by design flood ? What are the factors affecting the flood hydrograph ? Explain the procedure of using a unit hydrograph to develop the flood hydrograph due to a storm in a catchment.
 - (b) What is flood frequency analysis ? How flood frequency analysis at a project site is conducted ? What are the data requirements ?

ECE035/DNG-51799

3

[Turn Over

- (c) What do you mean by hydrologic reservoir routing ? Describe any two methods of hydrologic reservoir routing.
- 5. Attempt any two parts of the following : $(10 \times 2=20)$
 - (a) What are the differences between confined and unconfined aquifers for the determination of discharge with steady flow condition ? A well penetrates into an unconfined aquifer having a saturated depth of 100 m. The discharge is 250 litres per minute at 12 m drawdown. Assuming equilibrium flow conditions and a homogeneous aquifer, estimate the discharge at 18 m drawdown. The distance from the well where the drawdown influences are not appreciable may be taken equal for both cases.
 - (b) Describe an expression for discharge from a well fully penetrating a confined aquifer. Design a tubewell for the following data :

Yield required = 0.08 cumec, thickness of confined aquifer = 30 m, radius of circle of influence = 300 m, coefficient of permeability = 60 m/day and draw down = 5 m.

- (c) Write short notes on any four of the following :
 - (i) Well losses
 - (ii) Specific capacity and specific yield of an aquifer
 - (iii) Rain water harvesting
 - (iv) Aquifer and aquiclude
 - (v) Radius of influence and cone of depression.

ECE035/DNG-51799

4225

II-D